

JIS A 5513 角形じゃかご セトロン スピードオープンふとんかご

価 格 表

■ 使用材料 JIS G 3547 GH-3 (主母材)

規 格		長 さ			
用線	網目	高さ×幅	2m	3m	4m
3.2	10	40×120	6,900	10,350	13,800
		48×120	7,540	11,310	15,080
		64×120	8,320	12,480	16,640
	13	40×120	5,660	8,490	11,320
		50×120	5,960	8,940	11,920
		60×120	6,360	9,540	12,720
	15	40×120	5,220	7,830	10,440
		50×120	5,520	8,280	11,040
		60×120	5,920	8,880	11,840
4.0	10	40×120	9,220	13,830	18,440
		48×120	9,780	14,670	19,560
		64×120	10,860	16,290	21,720
	13	40×120	7,620	11,430	15,240
		50×120	8,120	12,180	16,240
		60×120	8,820	13,230	17,640
	15	40×120	6,980	10,470	13,960
		50×120	7,560	11,340	15,120
		60×120	8,240	12,360	16,480
5.0	13	40×120	11,700	17,550	23,400
		50×120	12,500	18,750	25,000
	15	40×120	10,220	15,330	20,440
		50×120	11,080	16,620	22,160
4.0	13	60×60	5,720	8,580	11,440
	15	60×60	5,320	7,980	10,640

■ 使用材料 JIS G 3547 GS-7 又は垂鉛アルミ合金めっき鉄線

規 格		長 さ			
用線	網目	高さ×幅	2m	3m	4m
4.0	10	40×120	12,220	18,330	24,440
		48×120	12,960	19,440	25,920
		64×120	14,400	21,600	28,800
	13	40×120	10,020	15,030	20,040
		50×120	10,660	15,990	21,320
		60×120	11,580	17,370	23,160
	15	40×120	8,520	12,780	17,040
		50×120	9,240	13,860	18,480
		60×120	10,080	15,120	20,160
5.0	13	40×120	14,940	22,410	29,880
		50×120	15,980	23,970	31,960
	15	40×120	12,360	18,540	24,720
		50×120	13,420	20,130	26,840
4.0	13	60×60	7,520	11,280	15,040
	15	60×60	6,520	9,780	13,040

(注) 垂鉛アルミ合金めっき鉄線 (10%アルミ) は、JISで定められた材料規格ではありません。